

# SET LAUFEN PRO NORDICS

## Floorstanding WC combination with cistern with fixing holes for floor fixation

82795.0



### TECHNICAL DATA

Order no.	82795.0
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 780 2 fixing holes with cistern flushing mechanism Impuls 720, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Special specification	with shut-off valve, Charge 781
Outlet	vertical
Weight	34,5 kg
Accessories excl.	Seat and cover, order no. 89095.0 Seat and cover with automatic lowering system, order no. 89095.1
Mounting acc. incl.	Fixing set, order no. 89175.7
Colours	see colour table

### SPECIFICATION TEXT

Floorstanding WC pan washdown LAUFEN PRO NORDICS, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)  
EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 450 mm  
outlet vertical 70 mm  
concealed fixation, 2 fixing holes  
Special feature: concealed surfaces directing water are fully glazed throughout, closed water rim, vacuum checked  
Further options / accessories: Surface refinement LCC, with shut-off valve option 781, WC seat and cover, 89095.0, WC seat and cover with automatic lowering 89095.1  
Order no. 82795.0

### TECHNICAL DRAWINGS / S 1 : 20

