

**Floorstanding WC rimless combination with cistern  
with fixing holes for floor fixation  
82896.6**



**TECHNICAL DATA**

Order no.	82896.6
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 737 2 fixing holes with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Outlet	vertical
Weight	41,5 kg
Accessories excl.	Seat, order no. 89115.3 Seat and cover, order no. 89095.0, 89115.0, 89115.2 Seat and cover with automatic lowering system, order no. 89095.1, 89115.1
Mounting acc. incl.	Fastening kit, order no. 89175.7
Colours	see colour table

**SPECIFICATION TEXT**

Floorstanding WC rimless washdown LAUFEN PRO N, sanitary ceramic,  
with cistern Dual-Flush (4,5/3-l-flush)  
EN 997, 4,5/3-l-flush, dimensions 365 x 650 x 890 mm  
outlet vertical 70 mm  
concealed fixation, 2 fixing holes  
Special feature: concealed surfaces directing water are fully glazed  
throughout, open water rim, vacuum checked  
Further options / accessories: Surface refinement LCC, WC seat 89115.3,  
WC seat and cover 89095.0, 89115.0, 89115.2, WC seat and cover with  
automatic lowering 89095.1, 89115.1  
Order no. 82896.6

**TECHNICAL DRAWINGS / S 1 : 20**

